

AVAILABLE IN
9 DIFFERENT TYPE OPTIONS*



1 **AGRICULTURE TYRE**
■ Rear Tyre - 8.3x20
■ Front Tyre - 180/85D12

2 **TURF TYRE**
■ Rear Tyre - 33x15.5-16.5
■ Front Tyre - 23x8.5-12

3 **INDUSTRIAL (FLOTATION) TYRE**
■ Rear Tyre - 33x15.5-16.5
■ Front Tyre - 23x8.5-12

4 **AGRICULTURAL WIDE PLUS TYRE**
■ Rear Tyre - 280/70R20
■ Front Tyre - 180/85D12

5 **AGRIMAX TURF RT 333 GARDEN TYRE**
■ Rear Tyre - 320/65R18
■ Front Tyre - 240/60R12

6 **WIDER F- AGRI TYRE**
■ Rear Tyre - 280/70R18
■ Front Tyre - 23x8.5-12

7 **INDUSTRIAL (REGULAR) TYRE**
■ Rear Tyre - 12x16.5
■ Front Tyre - 23x8.5-12

8 **BASIC - AGRI TYRE**
■ Rear Tyre - 8.00x18
■ Front Tyre - 5.00x12

9 **AGRICULTURAL WIDE TYRE**
■ Rear Tyre - 280/70R18
■ Front Tyre - 6.5/80-12




*Dimensions, Speed and Weight will vary with tyre option chosen.




Italian Designed
Lion Face



Hydrostatic
Power Steering




Engine : Stage III
Mitsubishi 3 Cylinder



Front Opening
Bonnet



Powerful
Hydraulics



Ergonomic Seating &
Footboard Area



Multi Disc
Oil Immersed Brakes



Differential
Lock

CAPTAIN AGRI MACHINERY EXIM LLP
Exports Arm of **CAPTAIN TRACTORS PVT. LTD.**

Veraval (Shapar), District : Rajkot (Gujarat) INDIA. Pincode - 360024.
Ph./Landline : + 91 281 299 4386, Mo : +91 99250 40445, Email : exports@captaintractors.com

www.captainagri.com

ENG

CAPTAIN

20-30 HP Small Tractors Series



CAPTAIN
■ AGRI MACHINERY ■



THE **ROAR** GETS **LOUDER**
FROM THE **LAND OF LIONS**

UNSTOPPABLE
In Every **CONDITION**



www.captainagri.com

CAPTAIN

20-30 HP Small Tractors Series

MODEL	CAPTAIN 201 4WD	CAPTAIN 223 4WD	CAPTAIN 282 4WD	CAPTAIN 283 4WD	CAPTAIN 303 4WD
ENGINE					
Engine HP Category	17	22	26	27	29
Engine Type	Captain CT-195	Mitsubishi L3E, Stage - III	Simpson - SC213	Mitsubishi MV S3L2, Stage - III	Mitsubishi MV-S3L2, Stage - III
No. of Cylinder	1	3	2	3	3
Capacity (CC)	947	953	1290	1318	1318
Rated Speed (RPM)	2200	3000	2500	2700±30	2800
Cooling System	Liquid Cooled	Liquid Cooled	Liquid Cooled	Liquid Cooled	Liquid Cooled
Bore / Stroke (mm)	102/116	76/70	95/91	78/92	78/92
Max. Torque(Nm)@RPM	65 (Nm) @ 1300-1500 RPM	52 (Nm) @ 2000 RPM	85.3 (Nm) @ 1400-1700 RPM	83 (Nm) @ 2200 RPM	79 +/-4 @1400-2200 RPM
TRANSMISSION					
Type	Sliding Mesh : Side Shift Gear Levers				
Gears	9 Forward, 3 Reverse (Options : Low, Medium or High Gear)				
PTO RPM	540 & 540 E				
Steering	Hydrostatic Power Steering				
Brake Type	Multi Disc Oil Immersed				
HYDRAULICS					
Hydraulic System	Auto Draft Sensing & Depth Control (2 Levers)				
Lift Capacity (Kgs.)	750 (at Lower Link Point)	850 (at Lower Link Point)	750 (at Lower Link Point)	750 (at Lower Link Point)	850 (at Lower Link Point)
No. of Pumps	1 (Tandem Pump)	1 (for Steering & Hydraulic System with Priority Valve)	1 (Tandem Pump)	2 (Total 28 LPM)	2 (Total 28 LPM)
Auxiliary Hydraulics	Trailer Hydraulic Tipping Single Outlet Standard Optional Kit available : 1 DA Auxiliary Hydraulics with 2 QRCs or 2 DA Auxiliary Hydraulics with 4 QRCs				
TYRE					
AGRICULTURAL TYRE					
Front	180/85D12				
Rear	8.30 x 20				
SPEED & DIMENSIONS [#]					
AGRICULTURAL TYRE					
Speed (km / hr.)	27.37	25.70	23.13	27.23	22.04
Size L x W x H (mm)	2650 x 1105 x 1335	2700 x 1080 x 1470	2680 x 1105 x 1360	2700 x 1080 x 1470	2700 x 1080 x 1470
Wheel Base (mm)	1450	1490	1490	1490	1490
Rear Track Center (mm)	811 to 988	811 to 988	811 to 988	811 to 988	811 to 988
Weight (kg)	905	900	1035	910	910

#+/- 5% Tolerance variations

Note : Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice.

CAPTAIN OF YOUR FARM

MODEL	CAPTAIN 280 DX - 4WD
ENGINE	
Engine HP Category	26
Engine Type	Simpsons - SC213
No. of Cylinder	2
Capacity (CC)	1290
Rated Speed (RPM)	2500
Cooling System	Liquid Cooled
Bore / Stroke (mm)	95/91
Max. Torque(Nm)@RPM	85.3 (Nm) @ 1400-1700 RPM
TRANSMISSION	
Type	Synchromesh
Gears	8 Forward. 2 Reverse
PTO RPM	Constant - 540 RPM
Steering	Power Assisted
Bake Type	Multi Disc Oil Immersed
HYDRAULICS	
Hydraulic System	Automatic Depth & Draft Control (2 Lever)
Lift Capacity (Kgs.)	600 (at Lower Link Point)
No. of Pumps	1 Tandem Pump
Auxiliary Hydraulics	Trailer Hydraulic Tipping Single Outlet Standard Optional Kit available : 1 DA Auxiliary Hydraulics with 2 QRCs or 2 DA Auxiliary Hydraulics with 4 QRCs
TYRE	
Front	7.00 x 16
Rear	11.2 x 24
SPEED & DIMENSIONS#	
Speed (km / hr.)	28.21
Size L x W x H (mm)	2720 x 1370 x 1000
Wheel Base (mm)	1550
Rear Track Center (mm)	1065
Weight (kg)	1125

Note : Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice.
Some accessories shown like , ROPS, Auxiliary Hydraulics, etc are optional.

HYDROSTATIC TRANSMISSION

Eazyto Operate

MODEL	CAPTAIN 283 H 4WD	CAPTAIN 303 H 4WD
ENGINE		
Engine HP Category	27	29
Engine Type	Mitsubishi MV-S3L2, Stage - III	
No. of Cylinder	3	
Capacity (CC)	1318	
Rated Speed (RPM)	2700	2800
Cooling System	Liquid Cooled	
Bore / Stroke (mm)	78/92	
Max. Torque(Nm)@RPM	83 (Nm) @ 2200 RPM	79 +/-4 @1400-2200 RPM
TRANSMISSION		
Type	Hydrostatic	
Gears	3 Forward / Reverse (Options : Low, Medium or High Gear)	
PTO RPM	Rear 540 / Mid 2000	
Steering	Hydrostatic Power Steering	
Brake Type	Multi Disc Oil Immersed	
HYDRAULICS		
Hydraulic System	Precision Control	
Lift Capacity (Kgs.)	900 (at Lower Link Point)	
No. of Pumps	2 (Total 28 LPM)	
Auxiliary Hydraulics	Trailer Hydraulic Tipping Single Outlet Standard Optional Kit available : 1 DA Auxiliary Hydraulics with 2 QRCs or 2 DA Auxiliary Hydraulics with 4 QRCs	
TYRE		
AGRICULTURAL TYRE		
Front	180/85D12	
Rear	8.30 x 20	
SPEED & DIMENSIONS#		
AGRICULTURAL TYRE		
Speed (km / hr.)	0 to 25	
Size L x W x H (mm)	2780 x 1080 x 2200	
Wheel Base (mm)	1550	
Rear Track Center (mm)	811 to 988	
Weight (kg)	1035	

Note : Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice.
Some accessories shown like , ROPS, Auxiliary Hydraulics, etc are optional.

#+/- 5% Tolerance variations