

Wide Range of SPEED OPTIONS

12 Different Speeds to choose from

L1(F) : 1.43 km/hr. @ Rated Engine RPM (Agri Tyre).

Suitable for land preparation.

H3(F) : 20.83 km/hr @ Rated Engine RPM (Agri Tyre).

Saves time during haulage & general transit.



up to 900 Kgs
(depending on model)

More Powerful HYDRAULICS

Easy Gear Shift WHILE USING LOADER

■ Easy gear shift from Reverse to 1st, & 1st to Reverse.

■ **Simultaneous Operation :**
Gear shifting on left hand side & loader operation on right hand side.

Eazy F1/R

More Versatile FRONT ATTACHMENTS

■ EU Manufactured Loader options available with Captain Compact Tractors.

■ The Euro quick hitch change for various Bucket / Fork Options.



Easily Connected



Powerful Lifting Capacity



Loader Friendly



Cabin option available from European supplier.

INTRODUCING

CAPTAIN

EU HOMOLOGATED TRACTOR MODELS

Model 223 | Model 263 | Model 263 MR | Model 263 **H**



THE **ROAR** GETS **LOUDER**
FROM THE **LAND** OF **LIONS**



CAPTAIN
AGRI MACHINERY

CAPTAIN AGRI MACHINERY EXIM LLP
Exports Arm of **CAPTAIN TRACTORS PVT. LTD.**

Veraval (Shapar), District : Rajkot (Gujarat) INDIA. Pincode - 360024.
Ph./Landline : + 91 281 299 4386, Mo : +91 99250 40445, Email : exports@captaintractors.com

www.captainagri.com



Powered by
MITSUBISHI
DIESEL ENGINE



www.captainagri.com

EU-ENGLISH

CAPTAIN

EU HOMOLOGATED TRACTOR MODELS

MODEL	CAPTAIN 223 4WD	CAPTAIN 263 4WD	CAPTAIN 263 4WD-MID ROPS	CAPTAIN 263 HST 4WD
-------	-----------------	-----------------	--------------------------	---------------------

ENGINE

Engine HP Category	22	25
Engine Type	Mitsubishi Stage - V L3E	Mitsubishi MVS3L2 Stage - V
No. of Cylinder	3	3
Capacity (CC)	953	1319
Rated Speed (RPM)	3000	2500
Cooling System	Liquid Cooled	Liquid Cooled
Bore / Stroke (mm)	76/70	78/92
Max. Torque(Nm)@RPM	52 (Nm) @ 2000 RPM	76.3 (Nm) @ 2000 RPM

TRANSMISSION

Type	Sliding Mesh : Side Shift Gear Levers	Sliding Mesh : Side Shift Gear Levers	Sliding Mesh : Side Shift Gear Levers	Hydrostatic
Gears	9 Forward, 3 Reverse	9 Forward, 3 Reverse	9 Forward, 3 Reverse	3 Forward / Reverse, Options : Low, Medium or High Gear
PTO RPM	540 & 540 E	540 & 540 E	540 & 540 E	Rear 540 / Mid 2000
Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
Brake Type	Multi Disc Oil Immersed	Multi Disc Oil Immersed	Multi Disc Oil Immersed	Multi Disc Oil Immersed

HYDRAULICS

Hydraulic System	Auto Draft Sensing & Depth Control (2 Levers)	Auto Draft Sensing & Depth Control (2 Levers)	Auto Draft Sensing & Depth Control (2 Levers)	Precision Control
Lift Capacity (Kgs.)	850 (at Lower Link Point)	850 (at Lower Link Point)	850 (at Lower Link Point)	900 (at Lower Link Point)
No. of Pumps	1 (for Steering & Hydraulic System with Priority Valve)	2 (One for Hydrostatic Steering & other for Hydraulic System)	2 (One for Hydrostatic Steering & other for Hydraulic System)	2 (Total 28 LPM)
Auxiliary Hydraulics	Trailer Hyd. Tipping Single Outlet Standard. Optional Kit available : 1 DA Auxiliary Hydraulics with 2 QRCs or 2 DA Auxiliary Hydraulics with 4 QRCs	1 DA Auxiliary Hydraulics with 2 QRCs Optional Kit available : Extra Secondary DA Auxiliary Hydraulics with 2 more QRCs	1 DA Auxiliary Hydraulics with 2 QRCs Optional Kit available : Extra Secondary DA Auxiliary Hydraulics with 2 more QRCs	1 DA Auxiliary Hydraulics with 2 QRCs Optional Kit available : Extra Secondary DA Auxiliary Hydraulics with 2 more QRCs



Italian Designed
Lion Face



Hydrostatic
Power Steering



Engine : Stage V
Mitsubishi 3 Cylinder



Front Opening
Bonnet



Powerful
Hydraulics



Ergonomic Seating &
Footboard Area



Multi Disc
Oil Immersed Brakes



Differential
Lock

SUITABLE FOR ALL WEATHER

FIELD CROPS OR ORCHARDS



TYRE OPTIONS	AGRICULTURAL	TURF	INDUSTRIAL / FLOTATION	AGRICULTURAL WIDE PLUS	AGRIMAX TURF RT 333 GARDEN	WIDER F-AGRI	INDUSTRIAL (REGULAR)	BASIC AGRI
Front	180/85D12	23 x 8.5 - 12	23 x 8.5 - 12	180/85D12	240/60R12	23 x 8.5 - 12	23 x 8.5-12	5.00 x 12
Rear	8.30 x 20	33 x 15.5 - 16.5	33 x 15.5 - 16.5	280/70R20	320/65R18	280/70R18	12 x 16.5	8.00 x 18

SPEED & DIMENSIONS*	CAPTAIN 223 4WD							
Speed Rounded Off (km / hr.)	24	22	22	24	23	22	22	21
Size L x W x H (mm)	2700 x 1080 x 2100	2700 x 1390 x 2050	2700 x 1390 x 2050	2700 x 1167 x 2095	2700 x 1220 x 2080	2700 x 1220 x 2060	2700 x 1264 x 2050	2700 x 1050 x 2060
Wheel Base (mm)	1490	1490	1490	1490	1490	1490	1490	1490
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	883 to 988	845 to 988	939	743 to 988
Weight (kg)	900	942	970	931	931	906	944	879

SPEED & DIMENSIONS*	CAPTAIN 263 4WD							
Speed Rounded Off (km / hr.)	20	18	19	20	19	18	19	18
Size L x W x H (mm)	2700 x 1080 x 2100	2700 x 1390 x 2050	2700 x 1390 x 2050	2700 x 1167 x 2095	2700 x 1220 x 2080	2700 x 1220 x 2060	2700 x 1264 x 2050	2700 x 1050 x 2060
Wheel Base (mm)	1490	1490	1490	1490	1490	1490	1490	1490
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	883 to 988	845 to 988	939	743 to 988
Weight (kg)	950	992	1020	981	981	956	994	929

SPEED & DIMENSIONS*	CAPTAIN 263 4WD - MID ROPS							
Speed Rounded Off (km / hr.)	20	18	19	20	19	18	19	18
Size L x W (mm)	2700 x 1080	2700 x 1390	2700 x 1390	2700 x 1167	2700 x 1220	2700 x 1220	2700 x 1264	2700 x 1050
Height - with Front ROPS UP (mm)	2190	2140	2140	2185	2170	2150	2140	2150
Height - with Front ROPS Folded Down(mm)	1474	1424	1424	1469	1454	1434	1424	1434
Wheel Base (mm)	1490	1490	1490	1490	1490	1490	1490	1490
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	883 to 988	845 to 988	939	743 to 988
Weight (kg)	1008	1050	1078	1039	1039	1014	1052	987

SPEED & DIMENSIONS*	CAPTAIN 263 HST 4WD							
Speed Rounded Off (km / hr.)	0 to 22	0 to 21	0 to 21	0 to 22	0 to 21	0 to 21	0 to 21	0 to 20
Size L x W x H (mm)	2780 x 1080 x 2200	2780 x 1390 x 2147	2780 x 1390 x 2153	2780 x 1167 x 2181	2780 x 1270 x 2167	2780 x 1220 x 2154	2780 x 1264 x 2161	2780 x 1050 x 2171
Wheel Base (mm)	1550	1550	1550	1550	1550	1550	1550	1550
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	951 to 988	883 to 988	939	811 to 988
Weight (kg)	1035	1077	1105	1066	1066	1041	1079	1014

#+/- 5% Tolerance variations

Note : Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice.

ALSO AVAILABLE MATCHING IMPLEMENTS

